

# iluminar

## WL105-PoE-2 Series

### Product Features

- Short range White Light illuminator
- Visible light for color
- SMT LED technology
- Distances up to 105' (32m)
- Angles 10°, 30°, 60°, 100° & 120°
- Low power consumption (12W)
- Even illumination
- Long life
- 5 year warranty
- IP67 weatherproof rating
- Built-in photocell on/off
- Telemetry input for remote switching
- PoE (IEEE 802.3af compliant) power



### What is White Light?

White light is visible light. Visible light provides the following benefits:

- Acts as a deterrent
- Allows for color images 24/7
- Lights up an area for safety
- True color video versus sodium lighting

All Iluminar White Light illuminators provide superior white lighting for video surveillance systems. They are available with a range of angles to cover different distances and scenes.

Supplied with an IP67 rating, they are vandal proof and can be used indoors and outdoors. The anodized aluminum housing provides protection from the harshest weather conditions.

### Professional Illuminators vs Camera Built-in Illuminators

There are many advantages of using separate, professional illuminators versus built-in camera infrared illuminators

- Longer life on the LED's
- No hot spots
- Wider angles
- Longer range
- Avoids attracting insects to obscure camera view

## Models

Model Number	Angle	Distance		HOV	
WL105-10-PoE-2	10°	82'	25m	14'	4m
WL105-30-PoE-2	30°	46'	14m	25'	8m
WL105-60-PoE-2	60°	33'	10m	38'	12m
WL105-100-PoE-2	100° x 50°	28'	8m	63'	19m
WL105-120-PoE-2	120°	23'	7m	80'	24m

## General

Electronics	High efficiency surface mount high power LED's with advanced current limited integral control circuitry
Number of SMT LED's	4
Construction	Robust high quality aluminum extrusion
Front window	Clear Polycarbonate
Finish	Black anodized
Power Cable	IP67 rated RJ45 Cat5e
Telemetry Following Contact	Via cable
Pressure Equalization Vent	Prevents thermal expansion & pressure cycling
Photocell	Adjustment via Remote
Illumination	Adjustable via Remote
Operating Temperature	-58° to 140°F (-50° to 60°C)
Weight	1.63lbs (0.5kg)
Dimensions	2.16" x 4.33" x 3.15" (55 x 110 x 80mm)
Mount	Black powder coated stainless steel wall mount

Power over Ethernet (PoE) IEEE802.3af compliant

Consumption 12W

## Lighting Output

Lumen Output	928lm
Wavelength	Visible Spectrum (400-750nm)
Color Temperature	6500K
Color Rendering Index (CRI)	74-80+

## Certifications

Safety	EN60598:2004 EN60825-1	Electrical Safety Laser Eye Safety
IP	IP67 in accordance with EN60529:1992	
EMC	EN61000, FCC part 15.107 15.108 Class B	
WEEE	Waste Electrical & Electronic Equipment European directive 202/96/EC	
RoHS	Restriction of Hazardous Substances European directive 202/95/EC	

## Electrical